

USAGE: FLAT AND RAISED FACED DIAMETER FLANGES UP TO AND INCLUSIVE OF CLASS 2500.

## Materials and Maximum T Limits

Spiral Wound Filler Guide	Filler Type				
	Thermiculite 835	Flexicarb	PTFE	Flexite Super	Ceramic
Maximum Temperature	1800°F 982°C	842°F 450°C	500°F 260°C	480°F 249°C	2300°F 1260°C
Minimum Temperature	-400°F -240°C	-400°F -240°C	-300°F -184°C	-150°F -101°C	-150°F -101°C

## Technical Benefits

- Metallic winding suited for cyclic loading
- Outer ring center gasket
- Inner/outer ring provides additional blow-out strength
- Inner/outer ring provides a compression stop
- Prevents flange erosion
- Prevents inward buckling
- Reduces turbulent flow
- Recommended for high pressure/temperature applications

## Design Parameters

Gasket Thickness	Maximum Inside Dimension	Recommended Flange Width	Recommended Compressed Thickness
0.125"	up to 20"	1"	0.090" / 0.100"
0.125"	20" to 40"	3/4"	0.090" / 0.100"
0.175"	up to 40"	1"	0.125" / 0.135"
0.175"	40" - 60"	1"	0.125" / 0.135"

Gasket Thickness	Maximum Inside Dimension	Recommended Flange Width	Recommended Compressed Thickness
0.175"	60" to 70"	7/8"	0.125" / 0.135"
0.175"	70" to 75"	3/4"	0.125" / 0.135"
0.250"	90"	1"	0.180" / 0.200"
0.285"	185"	1"	0.200" / 0.220"

## Required Surface Finish

- 125 - 250 Microinch Ra

## Tolerance Capabilities

Gasket Diameter	Inside Diameter	Outside Diameter
Up to 10"	± 1/64"	± 1/32"
10" to 24"	± 1/32"	± 1/16"
24" to 60"	± 3/64"	± 1/16"

## Applicable Standards

- ASME B16.20
- BS3381
- Suited for ASME B16.5 and B16.47 series flanges

## Design Factors

ASME (All)	
m	3
y	10,000 psi

PVRC	Flexicarb / SS	Flexite / SS
Gb (psi)	2300	2600
a	0.237	0.230
Gs (psi)	13	15

This Data Sheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. The acquisition of additional information may necessitate revisions to parts or all of this Data Sheet, and such information will be supplied as it becomes available.

As the Company's products are used for a multiplicity of purposes, and as the Company has no control over the method of their application or use, the Company excludes all conditions or warranties, express or implied, by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the Company and the Customer is given for the Customer's assistance only and without liability on the part of the Company.



# FLEXSEAL INDUSTRIAL

A FULL LINE GASKET & O-RING SUPPLIER

A Flexitallic® Distributor

**CALL** 832-445-0000

**FAX** 832-445-0002

**EMAIL** [sales@flexsealindustrial.com](mailto:sales@flexsealindustrial.com)

**VISIT** [www.flexsealindustrial.com](http://www.flexsealindustrial.com)

## 24/7 EMERGENCY CALLOUT SERVICE

Flexseal Industrial is a full line gasket and o-ring distributor. We provide a broad range of products including but not limited to Flexitallic spiral wound gaskets, die cut gaskets, sheet material, Flexpro (kammprofile) gaskets, RTJ's and o-ring seals.

We offer superior customer service and are committed to meeting the needs of all your industrial sealing applications.

### SPIRAL WOUND GASKETS



**SIGMA**



**Thermiculite**  
innovative. versatile. complete.



**Flexpro™**



**-RINGS**